

TECHNICAL SPECIFICATIONS FOR THE 2015 DOVE P1 (UNILAG EDITION).

DIMENSIONS: (2330\* 1120\* 820)mm

GROUND CLEARANCE: 180mm

CHASSIS: TUBULAR SPACE FRAME, MILD STEEL, 1\*1 INCH, 2mm THICK.

SUSPENSION (FRONT): DOUBLE WISHBONE/CONTROL ARM. BAJAJ 125CC SHOCK-ABSORBERS.

SUSPENSION (REAR): MULTI-LINK (THREE LINK) SUSPENSION SYSTEM.

STEERING: RACK AND PINION SYSTEM WITH 270DEG TURN LOCK TO LOCK.

ELECTRIC MOTOR: DC MOTOR, 24V, 120A, 2400RPM, 6Nm, 2.2kW.

BATTERY: 2 UNITS 12V 75AH, LEAD ACID.

TRANSMISSION: SINGLE SPEED, FIXED RATIO 1:5.8

TIRES: 16" WITH 12" RIMS

BRAKES: SINGLE PISTON HYDRAULIC DRUM BRAKE SYSTEM.

PERFORMANCE: TOP SPEED 35KM/H(est), RANGE 22KM(est)

WEIGHT: 190-200KG (est). (Net Weight with Fluids, Batteries, No Driver)

BODY: FIBRE GLASS, OPEN TOP.

STYLING: SINGLE SEAT, OPEN TOP CONCEPT.





