

8

7

6

5

4

3

2

1

D

D

C

C

B

B

A

A

8

7

6

5

4

3


2

1


NOTES (UNLESS OTHERWISE SPECIFIED):

1. MATERIAL : FR-4
2. NUMBER OF LAYERS: 4
3. FINISH: HOT AIR SOLDER LEVELED (HASL)
4. SOLDER MASK BOTH SIDES WITH LIQUID PHOTO IMAGEABLE SOLDER MASK (LPI), GREEN.
5. SILKSCREEN TOP AND BOTTOM SIDE WITH WHITE EPOXY NON CONDUCTIVE INK. SILKSCREEN MAY BE TRIMMED OFF ANY SOLDERED ENTITY.

DETAIL 'A'  
STACKUP



NOTE: NOMINAL THICKNESS = 40 MILS (+/-10%)



DRILL CHART: TOP to BOTTOM				
ALL UNITS ARE IN MILS				
FIGURE	SIZE	TOLERANCE	PLATED	QTY
•	12.0	+0.0/-12.0	PLATED	25
•	31.0	+3.0/-3.0	PLATED	4

CONTRACT NUMBER		<div style="text-align: center;"> <h1>SOLARCYCLE</h1> </div>			
PREPARED	DATE				
VREIMERS	08/12	<div style="text-align: center;"> <h2>TITLE</h2> <h1>FABRICATION DRAWING</h1> <h1>POWER CORE</h1> </div>			
CHECKED					
APPROVED					
APPROVED					
APPROVED					
QA		SIZE	FSCM NO	DWG NO	REV
		D			2
REL		SCALE:			SHEET 1 OF 1