

Data Sheet

Fujitsu Mainboard D3003-S Mini-ITX

Industrial Series

AMD Embedded G-Series Platform for DDR3 1333/1066 SDRAM Memory (SO-DIMM)
And AMD FT1 Mobile Processor ("eOntario")

Enhanced operating temperature range from 0°C to 60°C

Chipset:

AMD A55E Controller Hub

Processors:

D3003-S1: AMD Single-Core T44R (1.2GHz/9W)

D3003-S2: AMD Dual-Core T56N (1.6GHz/18W)



D3003-S3: AMD Dual-Core T56N (1.6GHz/18W)

Memory:

DDR3 1333/1066 SDRAM (SO-DIMM)

Product Features:

ATI integrated graphics on board; VGA, DVI,
DisplayPort and Dual Channel LVDS support
HD Audio onboard
Dual GbE LAN onboard
Serial ATA III RAID onboard
mSATA socket support (for Embedded OS) onboard
USB 2.0 onboard
8 Bit GPIO onboard
Infineon TPM V1.2 onboard
Designed for fanless operation
Mainboard ready for EuP



Features and benefits

Board Size Mini-ITX: 6.7" x 6.7" (170 x 170 mm)

Chipset AMD Embedded G-Series / A55E Controller Hub

Memory

2 x SO DIMM Socket (1.5V), max. 8GB, Single Channel
DDR3-1066 (CL7) / DDR3-1333 (CL9) SDRAM, unbuffered, no ECC
Note: Effective memory speed depends on installed processor!

Processor

AMD FT1 Mobile T44R Single Core Processor (1.2GHz; 9W) ¹⁾ or
AMD FT1 Mobile T56N Dual Core Processor (1.6GHz/18W) ¹⁾²⁾

Power Specification

19-24V / 3A via DC-connector (rear I/O connector or onboard connector)
5V and 3.3V Supply Voltage on PCI Slot (PCI Rev. 2.3)
3.3V Auxiliary Supply Voltage on PCI Slot (Wake-Up Support)
Onboard CPU Core Voltage Regulator

Power Supply Requirements

for onboard components

Source	Voltage	Tolerance (max)	Mainboard Current (typ.)
DC-In	+ 19-24 V	+10% / -15 %	1 A

BIOS

AMI UEFI BIOS

modified and adapted by Fujitsu Technology Solutions; Recovery BIOS, SM-BIOS (DMI), BIOS Update via USB (stable user settings), Quick Boot, Logo Boot, Quiet Boot, Plug & Play, automatic DRAM and PCI Configuration, S.M.A.R.T. Suppoort, Advanced Power Management, ACPI S3 / S4 (Save-to-RAM / Save-to-Disk), Wake on time from S5; configurable LVDS support; EraseDisk

Security Features

Recovery BIOS, System and BIOS Password, Boot Sequence Control for each drive, Serial Port Access Protection, TPM 1.2 (Infineon), Boot Sector Virus Warning, Write Protection for Flash BIOS, Harddisk Password incl. "Silent Password" option (no keyboard entry required).

Special Features

Silent Fan	Independent temperature related processor fan and system fan supervision and control
System Guard	View and adjust Silent Fan features
Silent Drives	Noise reduction for optical and hard disk drive
Recovery BIOS	Restores a corrupted BIOS
Desk Update	Simple driver update with Driver&Utilities DVD
Multi Boot	Comfortable boot from any boot device

Designed for Industrial Applications

Longlife components for 24 / 7 use in industrial applications
Revision control & Extended Lifetime (up to 5 years)
Enhanced operating temperature range (0°C - 60°C) ²⁾

Audio

Realtek ALC 663, 5.1-channel, High Definition Audio


LAN

Realtek RTL 8111E, 10/100/1000 Ethernet controller, PXE- & WoL-support

Miscellaneous

- Board Support Package (BSP) for Windows XP embedded
- Evaluation BSP for Embedded Linux (emlix)

External Connectors



Mainboard Versions

	Processor	LVDS	DisplayPort
D3003-S1:	T44R SingleCore 9W	24Bit / DualChannel	--
D3003-S2:	T56N DualCore 18W	--	yes
D3003-S3:	T56N DualCore 18W	24Bit / DualChannel	--

Features

	D3003-S
Chipset	AMD A55E FCH
Board Size	Mini-ITX
VGA ³⁾ / DVI / DisplayPort ¹⁾ / LVDS / HDMI ³⁾	✓ / ✓ / ✓ / ✓ / ✓
Stereo Audio / Multichannel Audio	✓ / -
Buzzer / int. Speaker Support	✓ / -
Dual LAN Gbit / 100 Mbit / 10 Mbit	✓ / ✓ / ✓
LAN ASF / AoL / WoL / Boot	- / - / ✓ / ✓
SATA / ATA / RAID / mSATA	✓ / - / ✓ / ✓
FireWire™ / USB 2.0	- / ✓
FAN monitored & controlled CPU / AUX1 / AUX2	✓ / ✓ / -
TEMP monitored CPU / ONB1 / ONB2 / OFFB	✓ / ✓ / ✓ / -

Special Features

Silent Fan / Silent Fan LT / System Guard / Silent Drives	✓ / - / ✓ / ✓
Recovery BIOS / Desk Update / Multi Boot	✓ / ✓ / ✓
HDD Password / EraseDisk	✓ / ✓
Boot Logo Option	✓

Internal Connectors

DIMM Sockets (DDR3 1333/1066, SO-DIMM)	2
PCI Express x16 Slot for Graphics Card	-
PCI Express x1 Slot (requires riser card)	1
PCI Slot (32Bit, 33 MHz, Rev. 2.3)	1
Mini PCI Express Slot	-
SATA (600) / ATA / Floppy / CF Card / mSATA	2 / - / - / - / 1
S/PDIF (digital Audio) OUT / IN	1 / -
CD Audio Input	-
Frontpanel Audio (9-Pin) AC'97 / Azalia ⁴⁾	- / 1
FireWire™ (9-Pin, Intel standard header)	-
USB (2.0, ~480 MBit/s; 2 channels per connector)	2
Specific socket for internal USB stick	1
Serial (FIFO, 16550 compatible = COM2) ⁶⁾	1
FAN ⁵⁾ CPU / System (AUX1) / System (AUX2)	1 / 1 / -
SMBus (Case Temperature) / Intrusion (Case Open)	- / 1
LVDS Dual Channel / Backlight Inverter ¹⁾	1 / 1
Feature Connector (8 Bit General Purpose I/O)	1
Frontpanel (Power Switch, LEDs, Intel 10 pin header)	1
Onboard Power Output (+5V/2A, +12V/2A) for drives	1
Onboard (internal input) DC-In 19-24V / 3A	1
Power 20 pin (ATX) / 4 pin (12V processor supply)	- / -

External Connectors

VGA Sub D ³⁾ / DVI-I / HDMI ³⁾ / DisplayPort ¹⁾	- / 1 / - / 1
Audio In / Line out (or driver configuration)	1 / 1
LAN (RJ-45)	2
PS/2 Mouse / Keyboard	1 / 1
USB (2.0, ~480MBit/s)	4
Serial (RS232, FIFO, 16550 compatible) ⁶⁾	2
DC-IN (external input) 19-24V / 3A	1

1) See "Mainboard Versions" overview for stuffing details

2) Forced cooling required, see technical documentation for detailed requirements

3) Via optional DVI-I / VGA interface connector resp. DVI-I / HDMI interface connector

4) Support for AC'97 audio frontpanel possible via BIOS Setup option

5) CPU fan = 4 pin PWM, system fan = 4 pin PWM or 3 pin (selectable via BIOS Setup)

6) COM2 external and COM2 internal cannot be used simultaneously

7) With updated CPU-Stepping (C0) 1.65GHz are usable (Boost functionality)

More information

Fujitsu platform solutions

In addition to Fujitsu Mainboards Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure-as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing products

www.fujitsu.com/global/services/computing

- PRIMERGY: Industrial standard server
- SPARC Enterprise: UNIX server
- PRIMEQUEST: Mission-critical IA server
- ETERNUS: Storage system

Software

www.fujitsu.com/software/

- Interstage: Application infrastructure software
- Systemwalker: System management software

More information

Learn more about Fujitsu Mainboards, please contact your Fujitsu sales representative, Fujitsu business partner, or visit our website.
<http://ts.fujitsu.com/>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at:
www.fujitsu.com/global/about/environment



Copyright

Copyright © Fujitsu Technology Solutions
All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions
OEM Mainboard Sales
Email: oem-sales@ts.fujitsu.com

Website: <http://ts.fujitsu.com>
2011-07-05 CE EN

Copyright © Fujitsu Technology Solutions

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html