


**Features:**

- ◆ Capacity : 100-1500g
- ◆ Material: aluminum-alloy
- ◆ Type: Parallel beam type
- ◆ Defend grade: IP65
- ◆ Application : body scales, hand scales, kitchen scales, postal scales, fishing scales, baby body scales and other micro electronic weighing systems.

Electrical connection and Dimensions:(dimension unit: mm)

**Specifications:**

capacity	g	100, 150, 200	300,500,750	1000,1500
rated output	mV/V	0.6 ± 0.15	0.7 ± 0.15	1.0 ± 0.15
safe overload	%FS		150	
ultimate overload	%FS		200	
excitation voltage	Vdc		≤6	
combined error	%FS		0.05	
zero balance	%FS		± 0.1	
non-linearity	%FS		± 0.05	
hysteresis	%FS		± 0.05	
repeatability	%FS		± 0.05	
creep	%FS/3min		± 0.05	
input resistance	Ω		1090 ± 10	
output resistance	Ω		1000 ± 10	
insulation resistance	M Ω		≥ 2000 @ 50 Vdc	
operating temperature range	°C		-10 ~ +40	
compensated temperature range	°C		-20 ~ +60	
temperature coefficient of SPAN	%FS/10°C		± 0.1	
temperature coefficient of ZERO	%FS/10°C		± 0.1	
Corner correction	%FS		± 0.1	
Electrical connection	cable	4 color wire, Ø0.6 × 110 mm excitation(+):Red excitation(-):Black signal(+):Green signal(-):White		

※Ordering code: model-capacity- rated output-accuracy-defend grade- the length of cable