bever the state in the state in the state in the state in the state of the state in the state of the state of

In light introduction of the second design solutions and their application to specific this application to specific the second design between the second design to be applied as the second design to be second The second secon

that/appart approver and the part of the competition to the state of t

The following the second s patternesetepetiotalnTalescencecidee noteesiestikeliensadentimestatiinetviitssorioedesteestiesedianeing the patteropatinez condensitied engrilled fan all de light by system of a far less predictable, rate monotonic de opfice bisterio of an all de light by system of a far less predictable, rate monotonic For example, consider the following system description as a far less predictable and the system of the following system description and the following system description and the following system description and the system of the following system description and the system of the sy expensenersed and the second second

The pattern structure and behavior escribes deliverative terms to the sector of the se

a larger in the pattern. The next approximate the provided in the second secon

meeting design constraints effective/invaliante/cuentiestapistadagious/cettastablestingeus at a landemisting appropriate the propriet of the p

Paterni Den je guneri ben in the statistic state of the second sta barrann singer and the second signal and the meature was a second and signal and signal and second side of the signal and second side of the second second

Chabter 4 Soltware Desidu Vrchitectric and Batterus tor Empedded Shatewa 32 UC4: Modulul periferic sa permita controlul manual (prin conexiunea BL). Valoarea 96

elementul central pe aceeasi conexiune; aplicate este primita prin comunicatia de BL iar parametrii masurati vor fi trimisi ca

experimentala: Generare Semnal SPAB, Achizitie date masurate. UC5: Modulul periferic sa permita optiuni de executie de proceduri de identificare

functionare default (exp: comanda pe 0, outputurile puse pe pozitii safe) UC6: In cazul deconectarii de la modulul central, perifericul va intra intr-un mod de

UC7: Upgrade-ul software sa se realizeze prin bluetooth - (bootloader – FOTA).

OneNote Online

- a. Vizualizarea parametrilor instalatiei (starile in timp real a IO, valorile in timp real a comenzilor si iesirilor)
- b. Optiuni de comanda manula de la distanta
- c. Optiuni de configurare solutie de control dispozitiv periferic;
- d. Optiuni configurare experiment identificare;
- e. [optional] Solutie de control automat implementata in modulul central.
- f. [optional] Monitorizarea tuturor instalatiilor si comanda tututor intr-o structura ierarhica de control;