

# ELIZA Business Card Firmware Description


This directory contains the ELIZA Business Card firmware project. It is an STM32CubeIDE project. Note that the ST USB Device Library Middleware component has been removed since it is licensed for use with only ST silicon. The compiled binary files have also been removed since they contain this code. All other ST components are licensed "as-is".

However I'm a little proud of my work on this project so I share that here. I'm releasing my code "as-is" too with no warranty or guarantee of any sort in the hopes it will be helpful or at least amusing.

## Project Setup

The project was created around a STM32F042K6 chip because it has the same pinout as the 'F096 and seemed to have the clock generation and USB peripherals. However it has only 32KB of Flash and 6KB of RAM (as opposed to 256 KB of Flash and 24 KB of RAM). I used the configurator to set the pins, configure the clock, enable USB and the USB CDC serial port middleware. See below for screenshots showing my project configuration.


Using the internal 48 MHz HSI clock for USB.




Project setup uses default stack and minimum heap sizes.

Pinout & Configuration	Clock Configuration	Project Manager	Tools
Project	Project Settings Project Name: <input type="text" value="eliza"/> Project Location: <input type="text" value="C:\Users\djull\OneDrive\Documents\flashchip"/> <input type="button" value="Browse"/> Application Structure: <input type="text" value="Advanced"/> <input type="checkbox"/> Do not generate the main()		
Code Generator	Toolchain Folder Location: <input text"="" type="text" value="STM32CubeIDE"/> <input checked="" type="checkbox"/> Generate Under Root		
Advanced Settings	Linker Settings Minimum Heap Size: <input type="text" value="0x200"/> Minimum Stack Size: <input type="text" value="0x400"/>		
	Thread-safe Settings Cortex-MONS <input type="checkbox"/> Enable multi-threaded support Thread-safe Locking Strategy: <input type="text" value="Default - Mapping suitable strategy depending on RTOS selection."/>		
	Mcu and Firmware Package Mcu Reference: <input type="text" value="STM32F042K6Ux"/> Firmware Package Name and Version: <input type="text" value="STM32Cube FW_F0 V1.11.5"/> <input checked="" type="checkbox"/> Use latest available version		


I only use the USB pins and programming pins.




Sys setup is default too. I never used the serial debug (it probably wouldn't have worked on the non-ST part).



NVIC is default with enabled USB interrupt.



USB is enabled.



The USB\_DEVICE middleware library is configured in a pretty default way. No doubt my Descriptors are all kinds of wrong. But I made a grand total of 10 cards so I suspect that won't be a problem.

Pinout & Configuration | Clock Configuration | Project Manager | Tools

Software Packs | Pinout

USB\_DEVICE Mode and Configuration

Mode

Class For FS IP: Communication Device Class (Virtual Port Com)

Configuration

Reset Configuration

Parameter Settings | Device Descriptor | User Constants

Configure the below parameters :

Search (Ctrl+F)

Device Descriptor

VID (Vendor Identifier)	1155
LANGID_STRING (Language Identifier)	English(United States)
MANUFACTURER_STRING (Manufacturer Identifier)	danjuliodesigns, LLC

Device Descriptor FS

PID (Product Identifier)	22336
PRODUCT_STRING (Product Identifier)	ELIZA
CONFIGURATION_STRING (Configuration Identifier)	CDC Config
INTERFACE_STRING (Interface Identifier)	CDC Interface

Pinout & Configuration | Clock Configuration | Project Manager | Tools

Software Packs | Pinout

USB\_DEVICE Mode and Configuration

Mode

Class For FS IP: Communication Device Class (Virtual Port Com)

Configuration

Reset Configuration

Parameter Settings | Device Descriptor | User Constants

Configure the below parameters :

Search (Ctrl+F)

Basic Parameters

USB_D_MAX_NUM_INTERFACES (Maximum number of supported interfa...	1
USB_D_MAX_NUM_CONFIGURATION (Maximum number of supported co...	1
USB_D_MAX_STR_DESC_SIZ (Maximum size for the string descriptors)	512 bytes
USB_D_SELF_POWERED (Enabled self power)	Enabled
USB_D_DEBUG_LEVEL (USB Debug Level)	0: No debug message

Class Parameters

USB CDC Rx Buffer Size	1024 Bytes
USB CDC Tx Buffer Size	1024 Bytes

## Firmware locations

My code lives in the `Eliza` subdirectory. There are two modules.

1. `eliza.h` and `eliza.c` contain the port of the 1977 BASIC program. It's a bit hacky as it was a more-or-less direct copy of the original BASIC translated to C.
2. `virthost.h` and `virthost.c` contain a shim API to interface Eliza with a serial stream of some sort. In this case the USB CDC library middleware. These files came originally from my Eliza port used in the my retrocomputer.

The `Core` subdirectory contains the boilerplate main code. I modified `main.c` to call `eliza_setup()` and `eliza_loop()`.

The `USB_HOST` subdirectory contains the auto-generated code that provides a user API to the USB CDC library middleware. Specifically I modified the `App/usbd_cdc_if.h` and `App/usbd_cdc_if.c` files to support a pair of circular buffers to transfer data between the virthost functions and USB. I also added a flag that is controlled by the Line State so I know if a USB serial port is open or not.

## Programming the Flashchip part

To support programming the FCM32F096KCU6 I did the following things.

I modified the automatically generated linker script to support the larger memories.

```
/* Memories definition */
MEMORY
{
  RAM      (xrw)      : ORIGIN = 0x20000000,  LENGTH = 24K
  FLASH    (rx)       : ORIGIN = 0x80000000,  LENGTH = 256K
}
```

This allowed the build process to complete without errors. This has to be redone if the configurator is run again.

And, finally, I used a DAPlink programmer to load the hex file (I had to add hex as an output option in the project preferences) into the 'F096 via the PCB ICSP header. I connected a 3.3V supply on the DAPlink programmer to the V+ line to supply power.