



TODO:
 Remove I2C user bus
 Add resistors to console I/O
 Remove RTS/CTS
 Remove XO
 Hardware version bits
 Diode protect bulk caps
 Add aux power input JST-PH

Header	Pin	Signal	Header	Pin	Signal
I2C	27	I2C_SDA	27	ID_SD/BCM0	
	28	I2C_SCL	28	ID_SC/BCM1	
	3	EEP_SDA	3	SDA/BCM2	
	5	EEP_SCL	5	SCL/BCM3	
	7		7	GPCLK/BCM4	
	29		29	BCM5	
	26		26	CE1/BCM7	
	24		24	CE2/BCM8	
	21		21	MISO/BCM9	
	19		19	MOSI/BCM10	
SPI0	23	SPI0_CLK	23	SCLK/BCM11	
	32		32	PWM0/BCM12	
	8		8	PWM1/BCM13	
	10	CONSOLE_TX	10	RXD/BCM14	
	36		36	CE2/BCM16	
	14		14	CE1/BCM17	
	12		12	CE0/BCM18	
	35		35	MISO/BCM19	
	38		38	MOSI/BCM20	
	40		40	SCLK/BCM21	
SPI1	15		15	BCM22	
	16		16	BCM23	
	22	CONSOLE_RX	22	BCM24	
	37		37	BCM25	
	13		13	BCM26	
	11		11	BCM27	
	34		34		

